ANGLE FITTINGS

# 4-Hole 45 Degree Closed Strut Angle - Electro-Galvanized

SKU: FS-5144-45-E/G Item weight: 1.4 lbs

**WIDTH**
**1-5/8"**

**MATERIAL**
**Carbon Steel**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | FS-5144-45-E/G |
| **Width** | 1-5/8" |
| **Hole Diameter** | 9/16" |
| **Thickness** | 1/4" |
| **Hole Spacing End Distance** | 13/16" |
| **Hole Spacing Center to Center** | 1-7/8" |
| **Material** | Carbon Steel |
| **Finish** | Electro-Galvanized |
| **Standards** | Finish = ASTM B-633 (Type III SC1 (0.2 mil thickness)) & Material = ASTM A575 or ASTM A1011 Grade 33 |
| **Manufacturer Name** | Flex-Strut |
| **Additional Info** | Dimension A (See image 2): 45° |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/4-hole-45-degree-closed-strut-angle-electro-galvanized**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.