CHANNEL NUTS

5/16" Short Spring Nut - Electro-Galvanized

SKU: FS-5/16SS-E/G Item weight: 0.1 lbs

MATERIAL

Carbon Steel

SPECIFICATIONS

SKU	FS-5/16SS-E/G
Diameter	5/16"
Hole Diameter	5/16"
Thickness	3/8"
Threads Per Inch	18
Material	Carbon Steel
Finish	Electro-Galvanized
Type	Electro-Galvanized Carbon Steel
Standards	Finish = ASTM B-633 (Type III SC1 (0.2 mil thickness))
Manufacturer Name	Flex-Strut

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-16-short-spring-nut-electro-galvanized

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.