FLAT FITTINGS

5-Hole Splice Plate - Electro-Galvanized

SKU: FS-5010-E/G Item weight: 0.95 lbs

WIDTH
1-5/8"

MATERIAL
Carbon Steel

SPECIFICATIONS

SKU	FS-5010-E/G
Width	1-5/8"
Hole Diameter	9/16"
Thickness	1/4"
Hole Spacing End Distance	13/16"
Hole Spacing Center to Center	1-7/8"
Material	Carbon Steel
Finish	Electro-Galvanized
Standards	Finish = ASTM B-633 (Type III SC1 (0.2 mil thickness)) & Material = ASTM A575 or ASTM A1011 Grade 33
Manufacturer Name	Flex-Strut

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-hole-splice-plate-electro-galvanized

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.